

In the Claims:

Please amend claims 1-10 as follows:

AG
SUB
B1
54103-1051060

1. (Amended) A protective [Protective] headgear [(30)] equipped with an [electro-acoustic] electroacoustic communication device [(1)] comprising an acoustic pick-up [a sensor (2) such as a microphone,] and a speaker [receiver (3) arranged] in a case, further comprising:
5 [(4), while] connection means [(5, 53) are provided destined for attaching] to attach said case [(4)] to said headgear [(30)], [characterized in that] the connection means [(5, 53) constitute, additionally,] including a removable
10 connection between the case of the communication device and the headgear.

Sub 7
B1

2. (Amended) The protective [Protective] headgear [(30)] equipped with an [electro-acoustic] electroacoustic type communication device according to claim 1 [(1) characterized in that] wherein the case [(4) comprises] further includes:
5 an extension [(5) forming] that defines a connection tab which is engaged in a lateral guide [(53)] of complementary shape [of] in said protective headgear [(30)].

3. (Amended) The protective [Protective] headgear [(30)] equipped with an [electro-acoustic] electroacoustic type communication device [(1)] according to claim 2, [characterized in that it includes] further including:
5 an external principal shell [(31)] comprising two lateral wall portions [(37)] corresponding to zones occupied by [the] ears of a [the] user.

4. (Amended) The protective [Protective] headgear [(30)] equipped with an [electro-acoustic] electroacoustic type communication device [(1)] according to claim 3, [characterized in that] wherein the case [(4)] is disposed

A

~~Sub~~
~~C3~~⁵

5

5

SUB
B2

5

5

A

9. (Amended) The protective [Protective] headgear [(30)] equipped with an [electro-acoustic] electroacoustic type communication device [(1)] according to [any of the preceding claims, characterized in that] claim 1, wherein the case [(16)] comprises:

two slots [(19, 20)], a first cylindrical slot [(19) destined to receive] for receiving the acoustic pick-up [microphone sensor (2)] and a second cylindrical slot [(20)], of smaller diameter, [destined to accept] for receiving the speaker [receiver (3)].

10. (Amended) The protective [Protective] headgear [(30)] equipped with an [electro-acoustic] electroacoustic type communication device [(1)] according to claim 9, [characterized in that] wherein the acoustic pick-up [microphone sensor (2)] is [arranged] located above the speaker [receiver (3)].

54B
B7
AK
5
54B
B7
AK
5

A

Please add new claims 11-12 as follows:

A7
SUB
B3

11. A protective headgear comprising:
a shell having an interior and an exterior;
a deformable structure mounted to the shell interior
for supporting the shell on a user's head, the deformable
5 structure and the shell defining ear receiving areas;
at least one tab receiving guide mounted to the
shell adjacent one of the ear receiving areas;
a case having a tab which is selectively engagable
with the guide for removably mounting the case to the shell
10 adjacent the ear receiving areas;
a microphone/speaker assembly mounted in the case;
an RF transmitter/receiver assembly electrically
connected with the microphone/speaker assembly.

1012. The protective headgear according to claim 11
further including:

a chin strap connected with the shell;
an electrical cable connected between the
5 transmitter/receiver assembly and microphone/speaker assembly;
a cable guide which is (i) releasably interconnected
to an intermediate portion of the electrical cable and
(ii) releasably attached to the chin strap.